



Ovation F-915FC

A high-power, full-color Fresnel fixture utilizing an RGBAL LED system to project a bright, soft field of light with a versatile motorized zoom.

Suited for theatrical stages, broadcast studios, and event spaces that demand a high-quality, soft-edged wash with full-color mixing and precise zoom control.

- Features an advanced RGBAL LED system for a full spectrum of vibrant colors and whites.
- Delivers a versatile motorized zoom range, adjustable from a tight 17° to a wide 85° wash.
- Includes a virtual color wheel and variable CCT presets from 2800 K to 6500 K.
- Ensures smooth fades with 16-bit dimming and flicker-free output via adjustable PWM.
- Built for sound-sensitive environments with a virtually silent convection cooling system.
- Offers flexible control via DMX and RDM, plus onboard dials for manual adjustments.

SPECIFICATIONS

Optical

Light Source: 89 LEDs (18 red, 18 green, 16 blue, 16 amber, 21 lime)
3 W, (1.13 A), 3698 K, 50,000 hours life expectancy

Color Temperature (range): 2800 to 6500 K

CRI (3200 K): 90

Beam Angle: 17° to 54°

Field Angle: 30° to 85°

Zoom Range: 17° to 85°

Lumens (30°): 4,294

Lumens (73°): 6,661

Illuminance (30°): 1,980 lux @ 5 m

Illuminance (85°): 433 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 27 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 17.80 x 12.59 x 10.82 in (452 x 320 x 275 mm)

Weight: 19 lb (8.6kg)

Exterior Color: Black

Housing Material: Aluminum alloy, Aluminum die-cast

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 1, 3, 5, 7, 11, 13, 14 or 17

Modes/Personalities: 8 personalities (1, 3, 5, 7, 11, 13, 14, 17, HSV)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 4 units @ 120 V; 8 units @ 208 V; 8 units @ 230 V

Power and Current: 304 W, 2.576 A @ 120 V, 60 Hz

Power and Current: 293 W, 1.490 A @ 208 V, 60 Hz

Power and Current: 293 W, 1.358 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP20, dry location

Noise Levels:

Idle: 0.4 dB(A) @ 1 m

Auto: 16.8 dB(A) @ 1 m

On: 30.2 dB(A) @ 1 m

Off: 11.6 dB(A) @ 1 m

Silent: 18.8 dB(A) @ 1 m

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN
Neutrik® powerCON® cables
3-pin or 5-pin DMX Cables
Color Blending Filters: DF60X1D, DF20D
Ovation F 7.5" Barndoor V2
Ovation Pole Operated Yoke 2 – 8"
Seetronic Powerkon IP65 cables

What's Included

Ovation F-915FC
Seetronic powerkon IP65 power cord
Gel frame (7.5 in/191 mm accessories)