



STRIKE P38

A compact and powerful IP-rated blinder and strobe featuring a 90W warm white LED that emulates the classic amber shift of dimming incandescent lights.

Ideal for touring productions, outdoor festivals, and theatrical applications requiring a compact, weather-resistant blinder with a classic incandescent look and feel.

- Features a 90W warm white and 8 amber LEDs to deliver a high 92 CRI.
- Offers 16-bit dimming control for exceptionally smooth, incandescent-style fades.
- Built with an IP65-rated housing and direct power/DMX connections for outdoor reliability.
- Includes adjustable PWM to eliminate on-camera flicker for broadcast and recording.
- Delivers intense blinder and strobe effects with a variable rate up to 29 Hz.
- Supports both DMX and RDM protocols for flexible setup and remote configuration.

SPECIFICATIONS

Optical

Light Source: 1 LED (WW) 90 W, (1.19 A), 2688 K, 50,000 hours life expectancy.

Light Source: 8 LEDs (Amber) 5 W, (0.07 A), 50,000 hours life expectancy.

Color Temperature (at full): 2754 K

Color Temperature (at 10%): 1899 K

CRI: 92

Beam Angle: 27°

Field Angle: 51°

Lumens: 2,186

Illuminance: 325 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Strobe Rate: 0 to 29 Hz

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 11.93 x 10.27 x 7.25 in (303 x 261 x 184 mm)

Weight: 8.4 lb (3.8 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Accessory Holder/Gel Frame Size: 6.25 in (159 mm)

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 5-pin IP65 XLR

Cable Length (power): 5 ft (1.5 m)

Control

Protocol(s): DMX, RDM

DMX Channels: 1, 3, 4, 5 or 6

Modes/Personalities: 5 personalities (1ch, 3ch, 4ch, 5ch, 6ch)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 30 units @ 120 V; 50 units @ 208 V; 55 units @ 230 V

Power and Current: 54 W, .449 A @ 120 V, 60 Hz

Power and Current: 56 W, .267 A @ 208 V, 60 Hz

Power and Current: 58 W, .245 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Seetronic Powerkon power linking cables

5-pin IP or Non-IP DMX Cables

Ovation F6.25 Barndoor

What's Included

STRIKE P38

Seetronic Powerkon IP65 power cord

Gel frame (6.25 in/158.75 mm accessories)