

Vesuvio 4 IP

This IP53-rated vertical fogger creates powerful, illuminated atmospheric bursts with dual-zone RGBA LEDs, delivering a CO₂-style effect without needing compressed gas tanks.

It delivers extreme vertical or horizontal throw for the largest outdoor festivals, touring stages, and indoor environments that demand high-impact, tour-grade atmospheric effects.



- **Advanced Vertical Fogger** – Creates powerful vertical fog bursts, delivering a CO₂-style effect without the need for gas or tanks.
- **Outdoor-Ready Design** – Rated for temporary outdoor use, providing reliable operation in wet or damp environments.
- **High-Performance Output** – Engineered for extreme throw distances of up to 50 ft (15 m), ensuring maximum visual impact.
- **Dual-Zone RGBA Illumination** – Independently controlled LED zones enable creative color effects and dynamic visuals.
- **Rugged Flight Case Included** – Ships in a durable touring case for easy transport and protection during rental or live event use.
- **Flexible Control Options** – Operate via onboard full-color display, wireless RF handheld remote, or DMX integration.
- **Integrated Drainage System** – Simplifies post-use maintenance with quick water evacuation and easy cleanup.
- **USB-C Port** – Allows convenient software and firmware uploads for future updates.
- **QDF (Quick Dissipating Fluid) Required** – Ensures optimal performance and clean atmospheric effects.

SPECIFICATIONS

Optical *

Light Source: 37 LEDs (RGBA)

** These specifications are still being finalized. Speak to a salesperson for more information.*

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Low Fluid Shutdown: No

Standalone Color Mixing: No

Built-in Automated Programs: Yes/No

Construction / Physical

Dimensions: 20.79 x 13.82 x 17.32 in (528 x 351 x 440 mm)

Weight: 72.2 lb (32.75 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, stainless steel

Tank Capacity: 1.4 gal (5.3 l)

Fluid Consumption: 22 ml/min

IP Rating: IP53

Heat-up Time: 13 min

Maximum Runtime: 45-second bursts

Connections

Power Input: Seetronic Powerkon IP65

Data Connectors: 5-pin IP65 XLR

Cable Length (power): 5 ft (1.5 m)

Firmware upgrades: USB type-C

Control

Control Protocol: [DMX, RDM, RF Remote]

DMX Channels: 14

Modes/Personalities: 1 personalities (14)

On-Board Control: Yes

Included Remote: yes

Electrical

Input Voltage: 208 VAC, 60 Hz

Power and Current: 2167 W, 10.43 A @ 208 V, 60 Hz

Breaker Size: 16 A, 250 V

Required Accessories

Compatible Mounting Options: [140DX OMEGA BRACKET, M12 BOLT]
Quick Dissipating Fluid (QDF)

Optional Accessories

CTC-50G
CTC-50HCN
RIGLINK POWERKON CABLES
RIGLINK DMX CABLES

What's Included

Vesuvio 4 IP
Seetronic Powerkon Cable
2x Omega Brackets
Controllers: RF Remote